

### Description

Semi-transparent mounting paper with good dimensional stability and high resistance to moisture, for the transfer of die-cut or computer-cut letters and symbols.

### Adhesive

Natural rubber, medium adhesive strength.

### Area of use

The special composition of the adhesive enables problem-free transfer of die-cut or computer-cut letters and symbols using both dry and wet bonding techniques. Due to its high dimensional stability, it is especially suitable for the transfer of large letters and symbols with precise positioning. This mounting paper is suitable for almost all well-known types of glossy or matt-finished films.

### Technical data

<b>Thickness*</b> (film with adhesive)	110 micron
<b>Weight*</b> (with adhesive)	100 g/m <sup>2</sup>
<b>Adhesive power*</b> (FINAT TM 1, after 20min, stainless steel)	4 N/25 mm
<b>Tensile strength</b> dry	
along	5,4 N/15 mm
across	3,5 N/15 mm
<b>Tensile strength</b> wet, along	2,5 N/15 mm
<b>Elongation at break</b>	13,5%
<b>Shelf life</b> (20°C and 50% relative humidity)	6 months
<b>Application temperature</b>	> +10°C

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

