



TruColor Cotton FR

This material consists of 100% cotton with a matt surface and is only without backing available. This opac fabric is perfect for any indoor banners.

Usability

- Specially developed for solvent inks. Compatible with UV-curable inks as well.
- For brilliant colours ink settings must be optimized according to ink, printer and software instructions.
- From experience the optimum temperatur of the heaters should not exceed 40°C / 104°F. Higher temperatures may be useful however one has to decide each case on its merits as the drying of the ink depends also on ink limit, print speed and other factors. (Own print test are a must in this connection!)

Use for Indoor

- Textile wall hangings
- Display booths
- Indoor signs
- Shop/Show decorations
- Window draperies
- Window displays
- Curtains
- etc.

Characteristics

Material	100% cotton
Withness CIE 108 2°/D50	L*a*b* 96/0,95/-4,2
Weight/Thickness With backing	225g/m ² ; 0,33mm
Print side	Inkjet coated
Reverse side	without backing
Flame retardant Certificates	Germany: DIN-4102-B1 USA: NFPA 701 California: CA 1237 Spain: M1
Ink Limit (according to profiles)	Please make print tests Avoid <i>CMYK-black</i>

Compatibility

(Solvent ink):

- Mutoh
- OCÉ
- Nur
- Mimaki
- ColorSpan
- Scitex
- Vutek
- Gandinnovations
- Seiko
- etc

(UVcurable ink) :

- Vutek
- Zünd
- Inca
- 3M
- Mimaki
- Durst
- etc

Customs:

Dutycode: 5901 9000 **Description:** Textile fabrics coated with gum or amylaceous sub -stances, of a kind used for the outer covers of books or the like: of cotton

Printed with solvent and UV curable ink.

Please test the product to be sure that the final result will satisfy your expectations.